

freshrss

Installation Podman

```
podman pod create --name freshrss --restart=unless-stopped -p 127.0.0.1:7070:80
```

```
podman create --name freshrss-postgres-17-2-alpine --pod freshrss \  
  --restart=unless-stopped \  
  -v /srv/freshRss/podman-data/postgres:/var/lib/postgresql/data:Z \  
  -e POSTGRES_USER=freshrss \  
  -e POSTGRES_PASSWORD=freshrss \  
  -e POSTGRES_DB=freshrss \  
  postgres:17.2-alpine
```

```
podman create --pod freshrss \  
  -e TZ=Europe/Paris \  
  -e 'CRON_MIN=1,31' \  
  -e 'OIDC_ENABLED=1' \  
  -e 'OIDC_PROVIDER_METADATA_URL=https://auth.ppsfleet.navy/realms/Ppsfleet/.well-known/openid-  
configuration' \  
  -e 'OIDC_REMOTE_USER_CLAIM=preferred_username' \  
  -e 'OIDC_CLIENT_ID=freshrss' \  
  -e 'OIDC_CLIENT_SECRET=...' \  
  -e 'OIDC_CLIENT_CRYPTO_KEY=ploufploufplouf' \  
  -e 'OIDC_SCOPES=openid' \  
  -e 'OIDC_X_FORWARDED_HEADERS=X-Forwarded-Host X-Forwarded-Port X-Forwarded-Proto' \  
  -v /srv/freshRss/podman-data/data:/var/www/FreshRSS/data:Z \  
  -v /srv/freshRss/podman-data/extensions:/var/www/FreshRSS/extensions:Z \  
  --name freshrss \  
  freshrss/freshrss
```

Installation on host

Ne permet pas d'utiliser le SSO :/

```
useradd freshrss -m -s /usr/bin/fish -d /srv/freshRss/

mkdir /srv/freshRss/php-wsdlcache /srv/freshRss/php-opcache /srv/freshRss/php-session

semanage fcontext -a -t httpd_sys_script_exec_t '/srv/freshRss(/.*)?'
semanage fcontext -a -t httpd_sys_rw_content_t '/srv/freshRss/php-session(/.*)?'
semanage fcontext -a -t httpd_sys_rw_content_t '/srv/freshRss/php-wsdlcache(/.*)?'
semanage fcontext -a -t httpd_sys_rw_content_t '/srv/freshRss/php-opcache(/.*)?'
semanage fcontext -a -t httpd_sys_rw_content_t '/srv/freshRss/FreshRSS-(.*)/data(/.*)?'
semanage fcontext -a -t httpd_sys_rw_content_t '/srv/freshRss/logs(/.*)?'
```

cat /etc/php-fpm.d/freshrss.conf

```
listen = /run/php-fpm/freshrss.sock

php_admin_value[error_log] = /srv/freshRss/logs/php-fpm.error.log
php_admin_flag[log_errors] = on
php_admin_value[memory_limit] = 1024M

php_value[session.save_handler] = files
php_value[session.save_path]    = /srv/freshRss/php-session
php_value[soap.wsdl_cache_dir]  = /srv/freshRss/php-wsdlcache
;php_value[opcache.file_cache]  = /srv/freshRss/php-opcache
```

Extension

<https://github.com/aidistan/freshrss-extensions>

<https://github.com/christian-putzke/freshrss-pocket-button>

Révision #8

Créé 27 décembre 2024 22:10:57 par tjiho

Mis à jour 3 janvier 2025 00:01:29 par tjiho