

# freshrss

## Installation Podman

Doc: <https://github.com/FreshRSS/FreshRSS/blob/edge/Docker/README.md>

```
podman create --env-file ~/freshrss/env \  
-v /srv/freshRss/podman-data/data:/var/www/FreshRSS/data:Z \  
-v /srv/freshRss/podman-data/extensions:/var/www/FreshRSS/extensions:Z \  
-p 127.0.0.1:7070:80 \  
--name freshrss \  
freshrss/freshrss
```

## Installation on host

Ne permet pas d'utiliser le SSO :/

```
useradd freshrss -m -s /usr/bin/fish -d /srv/freshRss/  
  
mkdir /srv/freshRss/php-wsdlcache /srv/freshRss/php-opcache /srv/freshRss/php-session  
  
semanage fcontext -a -t httpd_sys_script_exec_t '/srv/freshRss(/.*)?'  
semanage fcontext -a -t httpd_sys_rw_content_t '/srv/freshRss/php-session(/.*)?'  
semanage fcontext -a -t httpd_sys_rw_content_t '/srv/freshRss/php-wsdlcache(/.*)?'  
semanage fcontext -a -t httpd_sys_rw_content_t '/srv/freshRss/php-opcache(/.*)?'  
semanage fcontext -a -t httpd_sys_rw_content_t '/srv/freshRss/FreshRSS-(.*)/data(/.*)?'  
semanage fcontext -a -t httpd_sys_rw_content_t '/srv/freshRss/logs(/.*)?'
```

cat /etc/php-fpm.d/freshrss.conf

```
listen = /run/php-fpm/freshrss.sock  
  
php_admin_value[error_log] = /srv/freshRss/logs/php-fpm.error.log
```

```
php_admin_flag[log_errors] = on
php_admin_value[memory_limit] = 1024M
```

```
php_value[session.save_handler] = files
php_value[session.save_path]    = /srv/freshRss/php-session
php_value[soap.wsdl_cache_dir]  = /srv/freshRss/php-wsdlcache
;php_value[opcache.file_cache]  = /srv/freshRss/php-opcache
```

# Extension

<https://github.com/aidistan/freshrss-extensions>

<https://github.com/christian-putzke/freshrss-pocket-button>

---

Révision #9

Créé 2024-12-27 21:10:57 UTC par tjiho

Mis à jour 2025-05-04 13:22:33 UTC par blacksponge